



Roscoflamex fire retardants have been formulated to meet the extreme needs of the entertainment industry, designed to treat the wide range of diverse materials used in scenery, props and costume construction. Roscoflamex products meet fire retardant standards as established by NFPA, ASTM, ANSI, and UL and have been approved by the CA Fire Marshall and New York City Fire Dept.

**Roscoflamex Paint Additive** can be added to most latex or vinyl water based paints in order to create a flame retardant paint film. Roscoflamex Paint Additive is useful for treating scenic materials that cannot easily be treated by other methods and for supplying the additional protection of a fire retardant paint coating.

- PRODUCT NO: 150 079PA 0008 - 1 8oz Jar (236 ml)  
150 079PA 1208 – Case of 12 Jars
- DESCRIPTION: Roscoflamex Paint Additive is a liquid flame retardant additive intended for use with most water based, latex or vinyl acrylic paints.
- APPEARANCE: Clear, un-pigmented liquid that will not affect the color of paint.
- USE: Mix with most latex or vinyl water based paints. Test for compatibility. Not suitable for use with metallic pigments.
- FINISH: Typically leaves no residue. Will not affect the consistency of the paint or paint finish.
- APPLICATION: Normal paint application. Follow paint manufacturer's recommendation for application. Minimum of two coats recommended to achieve a 3 mil dry film thickness.
- MIX RATIO: Add one jar of Paint Additive to one (1) US Gallon (3.875 L) of paint.
- HAZARD: May cause skin and eye irritation on some people. Use in a well ventilated area.
- COVERAGE: Estimated 300 square feet per gallon.
- DRYING: Allow to dry naturally or using forced hot air.
- COMPOSITION: Water soluble inorganic salts. Safe for professional use.
- CERTIFICATION: ANSI 2-55 Class 1; ASTM E-84 Class A, CA State Fire Marshall
- OTHER: pH – 7.1